



Standard design

Manufactured acc. to DIN 16876	
Length	6 m
Smooth ends	onesided with chamfer
Colour	black
Inner surface	smooth

Possible designs

Quality	DIN 16874
Length	1 m to 12 m
Coloured stripes	co-extruded
Colour	on request
Outer surface	coloured, co-extruded or solid dyed
Inner surface	inner grooves for reducing the cable pull-in forces
Labelling	acc. to customer specifications
Chamfer	two-sides or without

Item designation	Outer diameter (mm)	SDR type	Wall thickness (mm)	Pallet contents (m)	Weight (kg/m)
KSR 32 x 3,0 GE	32	11	3,0		0,272
KSR 40 x 3,7 GE	40	11	3,7		0,430
KSR 50 x 4,6 GE	50	11	4,6	1200	0,666
KSR 63 x 3,0 GE	63	21	3,0	1020	0,586
KSR 63 x 5,8 GE	63	11	5,8	1020	1,050
KSR 75 x 6,8 GE	75	11	6,8		1,470
KSR 110 x 3,4 GE	110	33	3,4	516	1,170
KSR 110 x 4,2 GE	110	26	4,2	516	1,430
KSR 110 x 5,3 GE	110	21	5,3	516	1,770
KSR 110 x 6,3 GE	110	17,6	6,3	516	2,080
KSR 110 x 10,0 GE	110	11	10,0	516	3,140
KSR 125 x 3,9 GE	125	33	3,9	408	1,510
KSR 125 x 4,8 GE	125	26	4,8	408	1,840
KSR 125 x 7,1 GE	125	17,6	7,1	306	2,660
KSR 140 x 4,3 GE	140	33	4,3	318	1,884
KSR 160 x 4,9 GE	160	33	4,9	234	2,420
KSR 160 x 6,2 GE	160	26	6,2	234	3,040